

Aerial Work Platforms » Diesel Powered Scissor Lifts » Diesel Powered Liftlux » 203-24

203-24

Diesel Powered Scissor Lifts Diesel Powered Liftlux

Features

- Renowned triple-beam scissor arm stack with exceptional rigidity for enhanced comfort
- Proportional drive control for ease of use
- Nivelux® self-leveling hydraulic jacks standard

Quick Specs

- Platform Height Elevated – 20.30 m
- Overall Width – 2.40 m
- Platform Capacity – 750 kg



203-24 Specifications

Performance Data

Platform Capacity	750 kg
Capacity on Extension	500 kg
Deck Extension	Hydraulic
Lift/Lower Time	95/60 seconds
Maximum Drive Height	18.00 m
Weight*	11,400 kg
Ground Bearing Pressure**	4.4 kg/cm ²
Drive Speed (Lowered)	3.5 km/h
Gradeability	25%
Turning Radius - Inside	1.20 m
Turning Radius - Outside	5.20 m
Tyre Size	IN 355/55 D625

Tyre Type	Foam Filled Lug Tread
Dimensions	
Platform Height - Elevated	20.30 m
Platform Height - Lowered	2.66 m
Platform Railing Height	1.10 m
Stowed Height (Rails Folded)	2.96 m
Platform Dimensions	2.30 m x 4.35 m
Platform Length Fully Extended	7.20 m
Overall Length	4.80 m
Overall Width	2.40 m
Wheelbase	3.13 m
Ground Clearance	0.24 m

Power System/Chassis

Axle Oscillation	n/a
Brakes	Spring Applied
Diesel Engine	Deutz D2011L03i (31kW)
Fuel Tank Capacity	90 L
Hydraulic Reservoir	135 L