

245-25

Diesel Powered Scissor Lifts Diesel Powered Liftlux

Features

- Renowned triple-beam scissor arm stack with exceptional rigidity for enhanced comfort
- Oscillating axle for enhanced terrain performance
- Nivelux® self-leveling hydraulic jacks standard

Quick Specs

- Platform Height Elevated – 24.50 m
- Overall Width – 2.50 m
- Platform Capacity – 750 kg



245-25 Specifications

Performance Data

Platform Capacity	750 kg
Capacity on Extension	750 kg
Deck Extension	Hydraulic
Lift/Lower Time	125/80 seconds
Maximum Drive Height	21.00 m
Weight*	16,300 kg
Ground Bearing Pressure**	6.0 kg/cm ²
Drive Speed (Lowered)	2.3 km/h
Gradeability	25%
Turning Radius - Inside	1.50 m
Turning Radius - Outside	6.20 m
Tyre Size	315/80 R22.5

Tyre Type	Foam Filled Lug Tread
------------------	-----------------------

Power System/Chassis

Axle Oscillation	15cm
Brakes	Spring Applied
Diesel Engine	Deutz D2011L04i (42kW)
Fuel Tank Capacity	90 L
Hydraulic Reservoir	260 L

Dimensions

Platform Height - Elevated	24.50 m
Platform Height - Lowered	3.14 m
Platform Railing Height	1.10 m
Stowed Height (Rails Folded)	3.24 m
Platform Dimensions	2.50 m x 5.35 m
Platform Length Fully Extended	7.80 m
Overall Length	5.78 m
Overall Width	2.50 m
Wheelbase	3.90 m
Ground Clearance	0.26 m